



Canadian Plywood Grades

GRADES	TYPICAL APPLICATIONS	PANEL GRADES Face • Inner Plies • Back			CHARACTERISTICS
		DFP	CSP	POPLAR	
SANDED Appearance Grade Panels	Furniture, cabinet doors, partitions, shelving and opaque paint finishes. Concrete forms – DFP only.	G2S Good 2 Sides A•C•A	S2S Solid 2 Sides A•C•A	A-A* A•C•A	Sanded. Best appearance both faces. May contain neat wood patches, wood inlays or synthetic patching material.
		G1S Good 1 Side A•C•C	S1S Solid 1 Side A•C•C	A-C* A•C•C	Sanded. Best appearance one side only. May contain neat wood patches, wood inlays or synthetic patching material.
UNSANDED Structural Grade Panels (Available with EASY T&G)	Underlayment directly under carpeting, linoleum, rubber and synthetic sheets or tiles and ceramic tiles.	SELECT TF Tight Face B+•C•C	SELECT TF Tight Face B+•C•C	-	Surface openings are filled. Typically touch-sanded.
		SELECT B•C•C			Uniform surface with minor open splits. May be touch-sanded.
	Roof and wall sheathing. Subflooring beneath plywood underlayment, hardwood flooring and concrete topping.	SHEATHING C•C•C			UnsanDED. Face may contain limited size knots, knotholes and other characteristics.
OVERLAID Medium Density Overlaid General Purpose Paint Grade	Sundecks, siding, soffits, signs, boats and other exterior painted applications.	MDO 2S Medium Density Overlaid 2 sides C+•C•C+			Smooth, resin-fibre overlaid surface. Best paint base.
		MDO 1S Medium Density Overlaid 1 side C+•C•C			

CANPLY Proprietary Products

PRODUCTS	TYPICAL APPLICATIONS	PANEL GRADES Face • Inner Plies • Back			CHARACTERISTICS
		DFP	CSP	POPLAR	
	Roof sheathing and decking for residential, commercial and industrial construction.	SELECT B•C•C	SELECT B•C•C	-	Milled with patented edge profile for easy installation and edge support without H-clips.
		SHEATHING C•C•C	SHEATHING C•C•C	-	
	Floor and heavy roof sheathing for residential, commercial and industrial construction.	SELECT TF Tight Face B+•C•C	SELECT TF Tight Face B+•C•C	-	Milled with patented edge profile for fast, easy installation.
		SELECT B•C•C			
		SHEATHING C•C•C			
OVERLAID CONCRETE FORM (COFI FORM SP PLUS)	Reusable concrete formwork for a high quality finish.	DFP Oiled and Edge-Sealed	-	-	Premium performance in the high loading and wet service conditions of concrete forming.

* A variety of other panel grades are also available per CSA O153 Poplar Plywood. + Permissible openings shall be filled.